

Function

Design Load

Seasonal Efficiency

Function	YES	Design Load	5,3	Kw	Seasonal Efficiency	SEER	6,1
Cooling	YES	Cooling	4,7	Kw	Cooling	SCOP(A)	4,0
Heating / Average Zone	-	Heating / Average Zone	-	Kw	Heating / Average Zone	SCOP(W)	-
Heating / Warmer Zone	-	Heating / Warmer Zone	-	Kw	Heating / Colder Zone	SCOPO	-
Heating / Colder Zone	-	Heating / Colder Zone	-	Kw			

Cooling

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	Pdc	5,300	Kw
Tj=30°C	Pdc	3,993	Kw
Tj=25°C	Pdc	2,444	Kw
Tj=20°C	Pdc	1,204	Kw

Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	EERd	3,12
Tj=30°C	EERd	4,41
Tj=25°C	EERd	7,28
Tj=20°C	EERd	11,46

Heating / Average Zone

Declared capacity for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	Pdh	4,140	Kw
Tj=2°C	Pdh	2,568	Kw
Tj=7°C	Pdh	1,676	Kw
Tj=12°C	Pdh	1,789	Kw
Tj=bivalent temperature	Pdh	4,140	Kw
Tj=operation limit	Pdh	4,219	Kw

Declared coefficient of performance for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	COPd	2,78
Tj=2°C	COPd	4,06
Tj=7°C	COPd	4,76
Tj=12°C	COPd	5,71
Tj=bivalent temperature	COPd	2,78
Tj=operation limit	COPd	2,56

Heating / Warmer Zone

Declared capacity for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	Pdh	-	Kw
Tj=7°C	Pdh	-	Kw
Tj=12°C	Pdh	-	Kw
Tj=bivalent temperature	Pdh	-	Kw
Tj=operation limit	Pdh	-	Kw

Declared coefficient of performance for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	COPd	-
Tj=7°C	COPd	-
Tj=12°C	COPd	-
Tj=bivalent temperature	COPd	-
Tj=operation limit	COPd	-

Bivalent Temperature

Heating / Average Zone	Tbiv	-7	°C
Heating / Warmer Zone	Tbiv	-	°C

Operating Limit Temperature

Heating / Average Zone	Tol	-15	°C
Heating / Warmer Zone	Tol	-	°C

Electricity Data

Electric power input in power modes other than 'active mode'

Off mode	P _{OFF}	0,009	Kw
Standby mode	P _{SB}	0,001	Kw
Thermostat off mode	P _{TO}	0,007	Kw
Crankcase heater mode	P _{CK}	0,0	Kw

Annual electricity consumption

Cooling	Q _{CE}	304	kWh/a
Heating / Average Zone	Q _{HE}	1638	kWh/a

Capacity control - Variable

Other Items

Sound power lever (indoor unit)	LWA	61	dB(A)
Sound power lever (outdoor unit)	LWA	65	dB(A)
Global warning potential	GWP	675	Kg CO ₂ eq
Rated air flow (indoor unit)	-	-	m ³ /h
Rated air flow (outdoor unit)	-	-	m ³ /h