

Indoor unit: V5MKI32-18WiFiR

Outdoor unit: U5MRS32-18



Function

Design Load

Seasonal Efficiency

Function	Design Load	Seasonal Efficiency
Cooling	5,3 Kw	SEER 6,1
Heating / Average Zone	4,8 Kw	SCOP(A) 4,0
Heating / Warmer Zone	- Kw	SCOP(W) -
Heating / Colder Zone	- Kw	SCOP© -

Cooling

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj	Pdc	Kw
Tj=35°C	5,543	Kw
Tj=30°C	3,965	Kw
Tj=25°C	2,625	Kw
Tj=20°C	1,392	Kw

Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj	EERd
Tj=35°C	3,20
Tj=30°C	4,76
Tj=25°C	8,72
Tj=20°C	15,47

Heating / Average Zone

Declared capacity for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj	Pdh	Kw
Tj=-7°C	4,203	Kw
Tj=2°C	2,751	Kw
Tj=7°C	1,733	Kw
Tj=12°C	3,521	Kw
Tj=bivalent temperature	4,203	Kw
Tj=operation limit	3,521	Kw

Declared coefficient of performance for Heating / Average Season, at indoor temperature 20°C and outdoor temperature Tj

Tj	COPd
Tj=-7°C	2,65
Tj=2°C	3,87
Tj=7°C	5,28
Tj=12°C	6,74
Tj=bivalent temperature	2,65
Tj=operation limit	2,35

Heating / Warmer Zone

Declared capacity for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj	Pdh	Kw
Tj=2°C	-	Kw
Tj=7°C	-	Kw
Tj=12°C	-	Kw
Tj=bivalent temperature	-	Kw
Tj=operation limit	-	Kw

Declared coefficient of performance for Heating / Warmer Season, at indoor temperature 20°C and outdoor temperature Tj

Tj	COPd
Tj=2°C	-
Tj=7°C	-
Tj=12°C	-
Tj=bivalent temperature	-
Tj=operation limit	-

Bivalent Temperature

Zone	Tbiv	°C
Heating / Average Zone	-7	°C
Heating / Warmer Zone	-	°C

Operating Limit Temperature

Zone	Tol	°C
Heating / Average Zone	-15	°C
Heating / Warmer Zone	-	°C

Electricity Data

Electric power input in power modes other than 'active mode'

Mode	Power	Kw
Off mode	P _{OFF}	0
Standby mode	P _{SB}	0,007
Thermostat off mode	P _{TO}	0,001
Crankcase heater mode	P _{CK}	-

Annual electricity consumption

Mode	Consumption	kWh/a
Cooling	Q _{CE}	278
Heating / Average Zone	Q _{HE}	1657

Capacity control - Variable

Other Items

Item	Value	Unit
Sound power lever (indoor unit)	LWA 56	dB(A)
Sound power lever (outdoor unit)	LWA 65	dB(A)
Global warning potential	GWP 675	Kg CO ₂ eq
Rated air flow (indoor unit)	-	m ³ /h
Rated air flow (outdoor unit)	-	m ³ /h



Contact details for obtaining more information Importer / Distributor in European Union
 Inventor A.G. S.A. / 24th km National Road Athens - Lamia & 2 Thoukididou Str., Ag. Stefanos, 145 65,
 Tel.: +30 211 300 3300, Fax: +30 211 300 3333 www.inventor.ac/en

Harmonised standard: EN 14511:2011

No 626/2011 No 206/2012

Calculation methods - Measurement standards: EN 14825