



Ionizator



Concept
Inovator




Clasa
Energetica



Flux de aer
in 4 directii



Wi-Fi
Standard



Modul
Ultra Silentis



Racire
la temperaturi
scazute (-10°C)



Filtru de praf
de mare
densitate



Programator
24 Ore



Functia
Sleep Mode



Miscare Automata
a Flapsurilor



Functia de
Memorare a
Pozitiei Flapsurilor



Functia
Hot Start



Mod
Turbo



Auto
Restart



Autodiagnosticare
a Erorilor



Detectare
Scurgere
Freon



2 Cai
de Scurgere a
Condensului



All
DC Inverter



R32
ECO Freon

Model			DRV132-09WF/ DRVO32-09	DRV132-12WF/ DRVO32-12	DRV132-18WF/ DRVO32-18	DRV132-24WF/ DRVO32-24
Capacitate Răcire (Btu/h)			9.000 (2.730-12.620)	12.000 (3.410-13.650)	18.000 (4.430-19.790)	24.000 (7.500-29.000)
Capacitate Răcire (kWatt)			2.6 (0.8-3.2)	3.5 (1.0-4.0)	5.0 (1.30-5.80)	7.0 (2.2-8.5)
Capacitate Încălzire (Btu/h)			11.000 (2.730-14.330)	14.500 (3.410-17.740)	18.150 (4.770-20.470)	28.000 (8.190-34.120)
Capacitate Încălzire (kWatt)			3.2 (0.8-4.2)	4.2 (1.0-5.6)	5.2 (1.4-6.0)	8.1 (2.40-10.0)
Eficiență Sezonieră (în conformitate cu EN14825)	Răcire	Pdesign (kW)	2.6	3.5	5.0	7.0
		Clasă Energetică	A+++	A+++	A++	A++
		SEER	8.5	8.5	6.1	7.1
		Consum energetic anual (kWh/an)	107	144	287	350
	Încălzire (Zona Medie)	Pdesign (kW)	2.4	2.8	4.6	5.6
		Clasă Energetică	A++	A++	A+	A+
		SCOP	4.6	4.6	4.0	4.0
		Consum energetic anual (kWh/an)	731	854	1.610	1.963
	Încălzire (Zona Caldă)	Pdesign (kW)	2.6	3.0	4.6	5.6
		Clasă Energetică	A+++	A+++	A+++	A+++
		SCOP	5.5	5.5	5.1	5.1
		Consum energetic anual (kWh/an)	662	756	1.263	1.537
Voltaj/Frecvență/Fază (V/Hz/Ph)			230/50/1	230/50/1	230/50/1	230/50/1
Intensitate curent (A)	Răcire	2.9 (0.9-6.7)	3.9 (1.4-6.7)	6.5 (1.8-8.9)	9.6 (3.2-13)	
	Încălzire	3.6 (1.3-7.2)	5.0 (1.3-7.2)	6.3 (2.3-11.3)	9.7 (3.2-13)	
Consum energetic (W)	Răcire	650 (200-1.500)	875 (300-1.500)	1.460 (400-2.000)	2.160 (700-2.900)	
	Încălzire	800 (300-1.600)	1.100 (500-1.600)	1.400 (520-2.500)	2.180 (700-2.900)	
Debit de aer (Turbo/Mare/Medie/Mică) (m³/h)			650/600/500/450	700/650/550/500	1.000/900/800/600	1.300/1.200/1.000/850
Nivel de zgomot [dB(A)]	Unitate Interioară (Mut/Mi/Me/Ma)		20/25/30/35	22/29/33/38	30/35/40/44	30/37/43/47
	Unitate exterioară		47	48	53	52
Nivel sunet [dB(A)]	Unitate Interioară		54	58	59	60
	Unitate exterioară		59	61	65	65
Tip compresor			ROTARY	ROTARY	ROTARY	ROTARY
Traseu lichid Traseu gaz			1/4" 3/8"	1/4" 3/8"	1/4" 1/2"	1/4" 1/2"
Cablul de alimentare Exterioară / Siguranțe (Noxmm²)/(A)			3x1.5/10	3x1.5/10	3x2.5/16	3x2.5/16
Cablul comunicare (Noxmm²)			4x1.5	4x1.5	4x1.5	4x1.5
Dimensiuni (LxIxA) (mm)	Unitate interioară		887/211/281	887/211/281	1.030/233/322	1.115/248/336
	Unitate exterioară		800/280/550	800/280/550	800/280/550	890/353/697
Greutate netă (kg)	Interioară/Exterioară		10.0/29.0	10.0/31.5	13.0/32.7	16.0/51.0
Agent frigorific/Încarcare (g)			R32/650	R32/940	R32/900	R32/1.200
Interval temperaturi funcționare (°C)	Răcire		-10~43	-10~43	-10~43	-10~43
	Încălzire		-15~24	-15~24	-15~24	-15~24