



Aria


Creeaza un mediu sanatos avand o senzatie de prospetime care te urmareste!



Ionizator



Filtru de sterilizare HEPA



Filtru cu tripla actiune



Follow me



Clasa energetica A++ pe racire



Flux de aer
in 4 directii



Wi-Fi
inclus



Golden
Fin



Hotel
Menu



Functionare
silentioasa



Performanta excelenta
pe incalzire la -15°C



Autocuratare
puternica



Controller
centralizat (optional)

Model		AR5VI-09WFI/ AR5VO-09	AR5VI-12WFI/ AR5VO-12	AR5VI-18WFI/ AR5VO-18	AR5VI-24WFI/ AR5VO-24	
Capacitate racire (Btu/h)		9.000 (3.500-11.000)	12.000 (2.800-14.200)	18.000 (11.570-20.130)	24.000 (7.200-28.000)	
Capacitate racire (kW)		2.64 (1.03-3.22)	3.52 (0.82-4.16)	5.28 (3.39-5.90)	7.03 (2.11-8.21)	
Capacitate incalzire (Btu/h)		10.000 (2.800-11.500)	13.000 (2.900-16.300)	19.000 (10.580-19.960)	25.000 (5.300-28.000)	
Capacitate incalzire (kW)		2.93 (0.82-3.37)	3.81 (0.85-4.78)	5.57 (3.10-5.85)	7.33 (1.55-8.21)	
Eficienta sezoniera (in conformitate cu EN14825)	Racire	Pdesign (kW)	2.7	3.5	5.3	7.0
		Clasa energetica	A++	A++	A++	A++
		SEER	6.9	7.0	7.0	6.5
		Consum anual de curent electric (kWh/an)	137	175	265	377
	Incalzire (clima medie)	Pdesign (kW)	2.7	2.9	4.1	4.9
		Clasa energetica	A+	A+	A+	A+
		SCOP	4.0	4.1	4.1	4.0
		Consum anual de curent electric (kWh/an)	946	992	1.401	1.717
	Incalzire (clima calda)	Pdesign (kW)	2.5	2.5	4.5	5.3
		Clasa energetica	A+++	A+++	A+++	A+++
		SCOP	5.3	5.4	5.1	5.1
		Consum anual de curent electric (kWh/an)	661	649	1.308	1.545
Voltaj/Frecventa/Faza (V/Hz/Ph)		220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1	
Intensitate curent (A)	Racire	3.22 (0.35-4.78)	4.96 (0.40-6.90)	6.70 (2.40-9.00)	10.90 (1.80-13.90)	
	Incalzire	3.40 (0.32-4.32)	4.68 (0.70-7.40)	6.50 (3.40-8.70)	9.30 (1.30-13.50)	
Consum energetic (kW)	Racire	0.74 (0.08-1.10)	1.09 (0.10-1.60)	1.55 (0.56-2.05)	2.51 (0.42-3.20)	
	Incalzire	0.78 (0.07-0.99)	1.05 (0.16-1.71)	1.50 (0.78-2.00)	2.13 (0.30-3.10)	
Debit de aer (Mare/Mediu/Mic) (m ³ /h)		416/309/230	584/477/395	730/500/420	1.020/830/640	
Nivel de zgomot [dB(A)]	Unitate interioara (Silentios/Mic/Mediu/Mare)	23/26/32/39	23/26/32/39	23/28/33/5/43	25/30/5/41.0/47	
	Unitate exterioara	56	56	55.5	60.5	
Putere sonora [dB(A)]	Unitate interioara	56	55	57	64	
	Unitate exterioara	63	63	65	67	
Volum dezumidificare	(L/h)	1.2	1.6	2.0	2.8	
	(L/zi)	28.8	38.4	48.0	67.2	
Tip compresor		ROTATIV	ROTATIV	ROTATIV	ROTATIV	
Traseu lichid Traseu gaz		1/4" 3/8"	1/4" 3/8"	1/4" 1/2"	3/8" 5/8"	
Sigurante (A)		10	10	16	16	
Cabluri de comunicare (Nr x mm ²)		5x1.5	5x1.5	5x1.5	5x2.5	
Dimensiuni (LxAxl) (mm)	Unitate interioara	722x187x290	802x189x297	965x215x319	1.080x226x335	
	Unitate exterioara	720x270x495	720x270x495	805x330x554	890x342x673	
Greutate neta (kg)		7.3/23.2	8.6/23.2	10.9/33.5	13.7/43.9	
Agent frigorific/Cantitate (g)		R32/550	R32/550	R32/1.100	R32/1.450	
Interval de functionare la temperaturi exterioare (°C)	Racire	-15~50	-15~50	-15~50	-15~50	
	Incalzire	-15~24	-15~24	-15~24	-15~24	