



The Ultimate  
*Care*  
for you!



Auto Restart  
Function



Auto  
Defrosting



Self Diagnosis  
& Auto Protection



24 h  
Timer



Transparent  
Water Level  
Indication



LED  
Display



Convenient  
Handle



Choose the right unit that suits your needs from a wide range of Inventor dehumidifiers. Inventor dehumidifiers are the right solution to putting an end to moisture.



silent

#### Digital Display

It displays the room's humidity level and the set humidity level.

#### Humidity Set

Control your desired humidity level by using the «+» and «-» keys.

#### Continuous Dehumidification

During the continuous dehumidification operation, the unit operates constantly removing the humidity from the air. Preset humidity levels will not be acknowledged by the unit during this operation.

#### Water Tank

The water tank is equipped with a window allowing for an easy assessment of the water level. When the water tank is full, the indicator P2 will be displayed on the screen and the device automatically shuts off, preventing overflow.

#### Ergonomic Handle

Easy movement and repositioning.

#### Auto Restart

After a power outage, the device will automatically start with the previous settings.

#### Turbo

For quick and direct dehumidification use the Turbo mode.

#### Continuous Drainage

For continuous drainage simply connect a hose from the unit to a drainage system.

#### Auto Defrost

Efficient operation even in cold spaces (up to 5°C).

#### SPECIFICATIONS

	Care
Dehumidifying Capacity (L/24h)	8
Control Type	Ηλεκτρονικός
Voltage / Frequency / Phase (V/Hz/Ph)	220-240 / 50 / 1
Power Input (W)	290
Current Input (A)	2
Water Tank Volume (L)	2
Air Flow (m³/h)	120
Noise Level (dB(A))	40/43
Dimensions WxDxH (mm)	308x247x456
Net Weight (kg)	11.2
Refrigerant	R134a/80g
Applicable room area (m²)	12 - 35
Operation Temperature Range (°C)	5oC - 35oC