











Defrosting

Time

Auto Restart Function





Self Diagnosis & Auto Protection







Transparent Water Level Indication



Display

Filter Cleaning



Choose the right unit that suits your needs from a wide range of Inventor dehumidifiers. Inventor dehumidifiers are the right solution to putting an end to moisture.



It displays the room's humidity level and the set hu-

Control your desired humidity level by using the «+»

During the continuous dehumidification operation, the

unit operates constantly removing the humidity from the air. Preset humidity levels will not be acknowl-

The water tank is equipped with a window allowing

for an easy assessment of the water level. When the

water tank is full, the indicator P2 will be displayed on the screen and the device automatically shuts off

Continuous Dehumidification

edged by the unit during this operation.

Digital Display

midity level.

Humidity Set

and «-» keys.

Water Tank

SPECIFICATIONS

, preventing overflow.





smart dehumidifing

dry laund

Ergonomic Handle

Easy movement and repositioning.

Auto Restart

After a power outage, the device will automatically start with the previous settings.

Turbo

For quick and direct dehumidification use the Turbo mode.

Continuous Drainage

For continuous drainage simply connect a hose from the unit to a drainage system.

Auto Defrost

Efficient operation even in cold spaces (up to 5°c).

	EVA - 16	EVA - 20
Dehumidifying Capacity (L/24h)	16	20
Control Type	Ηλεκτρονικός	Ηλεκτρονικός
Voltage / Frequency / Phase (V/Hz/Ph)	220-240 / 50 / 1	220-240 / 50 / 1
Power Input (W)	350	440
Current Input (A)	2.0	2.1
Water Tank Volume (L)	3	3
Air Flow (m³/h)	150	150
Noise Level (dB(A))	50	50
Dimensions WxDxH (mm)	350x245x510	350x245x510
Net Weight (kg)	13.5	13.7
Refrigerant	R134a/105g	R134a/120g
Applicable room area (m²)	29 - 90	37-120
Operation Temperature Range (°C)	5oC - 35oC	5oC - 35oC

