



24-Hours
Timer



Auto Swing



Self Evaporating
System



Sleep Mode



Auto Error
Diagnosis



Quick
Installation

MODEL	MAGIC	
Cooling Capacity (Btu/h)	11.942	
Cooling Capacity (kWatt)	3.5	
Heating Capacity (Btu/h)	9.895	
Heating Capacity (kWatt)	2.9	
Energy Class (Cooling/Heating)	A/A+	
EER	2.6	
COP	2.6	
Voltage / Frequency / Phase (V/Hz/Ph)	230/50/1	
Current Input (A)	Cooling	5.9
	Heating	5.0
Power Input (W)	Cooling	1.350
	Heating	1.130
Air Flow Volume (m ³ /h) (High/Medium/Low)	425/365/340	
Dehumidifying Volume (L/h)	1.2	
Noise Level (dB(A)) (Low/Medium/High)	52.4/52.7/53.7	
Sound Power Level (dB(A))	65	
Compressor Type	ROTARY	
Dimensions WxDxH (mm)	466x397x765	
Net Weight (kg)	34	
Refrigerant	R410A/420g	



A/A+ Energy Class



Cooling & Heating





MODEL	COOL
Cooling Capacity (Btu/h)	8.000
Cooling Capacity (kWatt)	2.34
Energy Class (Cooling)	A
EER	2.60
Voltage / Frequency / Phase (V/Hz/Ph)	230/50/1
Current Input - Cooling (A)	4.60
Power Input - Cooling (W)	900
Air Flow Volume (m³/h) (High/Medium/Low)	330/300/250
Dehumidifying Volume (L/h)	0.75
Noise Level (dB(A)) (Low/Medium/High)	50/52/54
Sound Power Level (dB(A))	65
Compressor Type	ROTARY
Dimensions WxDxH (mm)	300x345x790
Net Weight (kg)	24.00
Refrigerant	R410A/460g



Quick Installation



Low Noise Level



24-Hours Timer



Sleep Mode



Automatic Operation



Auto Restart



Auto Error Diagnosis



Lock

MODEL	EPIC
Cooling Capacity (Btu/h)	9.000
Cooling Capacity (kWatt)	2.64
Energy Class (Cooling)	A
EER	2.60
Voltage / Frequency / Phase (V/Hz/Ph)	230/50/1
Current Input - Cooling (A)	4.60
Power Input - Cooling (W)	1.015
Air Flow Volume (m³/h) (High/Medium/Low)	280/240
Dehumidifying Volume (L/h)	1.0
Noise Level (dB(A)) (Low/Medium/High)	51/53
Sound Power Level (dB(A))	65
Compressor Type	ROTARY
Dimensions WxDxH (mm)	345x355x703
Net Weight (kg)	23.8
Refrigerant	R410A/350g



Sleep Mode



Advanced Design



24-Hours Timer



Auto Restart



Self Evaporating System



Omni-Directional Caster



Auto Error Diagnosis



Window Kit

