





Ionizer



Triple Action
Filter



Active Carbon
Filter



Wi-Fi
Standard



Powerful Self-Cleaning



Antibacterial Protection



Golden Fin



Follow Me



Energy Class



Anti-cold Air Function




Low Temperature Heating at -15°C



Turbo Mode



Auto Swing Louver



Ultra Silence Mode



24-hour Timer



Sleep Mode



All DC Inverter



Refrigerant Leakage Detect



Auto Error Diagnosis



R32 ECO Refrigerant

MODEL		PFVI32-09WF / PFVO32-09	PFVI32-12WF / PFVO32-12	PFVI32-18WF / PFVO32-18	PFVI32-24WF / PFVO32-24	
Cooling Capacity (Btu/h)		9.200 (1.706-10.578)	12.200 (2.730-12.284)	18.400 (4.095-19.108)	24.500 (4.777-25.591)	
Cooling Capacity (kWatt)		2.7 (0.5-3.1)	3.6 (0.8-3.6)	5.4 (1.2-5.6)	7.2 (1.4-7.5)	
Heating Capacity (Btu/h)		10.200 (1.706-11.260)	12.600 (3.412-12.966)	19.700 (4.095-20.473)	24.500 (3.071-24.908)	
Heating Capacity (kWatt)		3.0 (0.5-3.3)	3.7 (1.0-3.8)	5.8 (1.2-6.0)	7.2 (0.9-7.3)	
Seasonal Efficiency (In accordance to EN14825)	Cooling	Pdesign (kW)	2.6	3.2	5.3	6.7
		Energy Class	A++	A++	A++	A++
		SEER	6.16	6.12	6.57	6.89
		Annual Power Consumption (kWh/year)	148	184	283	341
	Heating (Middle Zone)	Pdesign (kW)	2.5	2.7	4.4	5.7
		Energy Class	A+	A+	A+	A+
		SCOP	4.17	4.14	4.02	4.11
		Annual Power Consumption (kWh/year)	839	913	1.535	1.940
	Heating (Warm Zone)	Pdesign (kW)	2.6	3.4	5.5	7.0
		Energy Class	A+++	A+++	A+++	A+++
		SCOP	5.31	5.21	5.4	5.25
		Annual Power Consumption (kWh/year)	686	963	1.426	1.867
Voltage/Frequency/Phase (V/Hz/Ph)		220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1	
Current Input (A)	Cooling	3.55	4.82	7.32	9.75	
	Heating	3.33	4.30	6.61	8.67	
Power Input (W)	Cooling	800 (100-1.300)	1.090 (100-1.600)	1.650 (90-2.000)	2.200 (130-3.000)	
	Heating	750 (100-1.400)	970 (300-1.600)	1.490 (200-2.200)	1.960 (200-2.700)	
Air Flow Volume (Turbo/High/Medium/Low) (m³/h)		560/497/482/358	560/497/482/358	850/750/657/564	1150/1010/902/795	
Noise Level [dB(A)]	Indoor unit (Silent/Low/Medium/High)	25/31/37/44	26/33/39/44	30/36/41/47	31/37/43/48	
	Outdoor unit	51	52	56	58	
Sound Power Level [dB(A)]	Indoor unit	56	54	58	58	
	Outdoor unit	61	60	64	65	
Compressor Type		ROTARY	ROTARY	ROTARY	ROTARY	
Liquid line Gas line		1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	1/4" / 5/8"	
Power Supply Wire Outdoor / Fuses (Noxmm²)/(A)		3 × 1.5 / 10	3 × 1.5 / 10	3 × 2.5 / 16	3 × 2.5 / 16	
Signal Wires (Noxmm²)		5 × 1.0	5 × 1.0	5 × 1.5	5 × 1.5	
Dimensions (WxDxH) (mm)	Indoor unit	792x201x292	792x201x292	940x224x316	1132x232x330	
	Outdoor unit	730x285x545	730x285x545	800x315x545	900x350x700	
Net Weight (kg)	Indoor/Outdoor	8 / 25	8.5 / 25	12 / 35	15 / 45	
Refrigerant/Charge (g)		R32/530	R32/600	R32/1.280	R32/1.440	
Outdoor Operation Temperature Range (°C)	Cooling	16-47	16-47	16-47	16-47	
	Heating	-15-32	-15-32	-15-32	-15-32	